

HAZARDOUS BUILDING MATERIALS INSPECTION REPORT

OFFUTT AFB PROJECT: SGBP 20-0041 Repair HVAC B 324 - Redesign Offutt Air Force Base

November 22, 2022

Prepared for:

Schemmer & Associates
Omaha, NE

Prepared by:



AMI Environmental
8802 South 135th Street, Suite 100
Omaha, Nebraska 68138
AMIE # 22-275

State of Nebraska

Department of Health and Human Services
Division of Public Health

William H Crowe
Asbestos Inspector

License #: 1368

Status: Active

Expiration: 01/31/2021




TABLE OF CONTENTS

1. SURVEY OVERVIEW	1
1.1. Purpose and Scope	1
1.1.1. Inspection Area	1
1.1.2. Limitations	1
1.2. Regulatory Reference.....	2
2. BUILDING INFORMATION.....	2
2.1. General Construction.....	2
2.2. Pre-Existing Information.....	2
3. INSPECTION METHODOLOGIES.....	2
3.1. Asbestos Inspection	2
3.1.1. Key Definitions	2
3.1.2. Homogenous Material Numbering Convention	3
3.1.3. Bulk Sampling.....	3
3.2. Lead-Based Paint Inspection.....	4
3.2.1. Key Definitions	5
3.2.2. Homogenous Paint Applications Numbering Convention.....	5
3.2.3. Paint Chip Sampling	5
4. SUMMARY OF INSPECTION FINDINGS	5
4.1. Asbestos Inspection Findings	5
4.2. Lead-Based Paint Inspection Findings.....	5
5. RISKS AND HAZARDS.....	6
5.1. Asbestos.....	6
5.2. Lead-Based Paint.....	6
6. RECOMMENDATIONS.....	6
6.1. General Recommendations	6
6.1.1. Asbestos	6
6.1.2. Lead-Based Paint	7

6.2.	Hazardous Conditions Recommendations	7
6.3.	Point Count Analysis / TEM Chatfield Analysis Recommendations	7
7.	REGULATORY REQUIREMENTS.....	7
7.1.	Asbestos-Containing Materials	7
7.1.1.	Notification Requirements	7
7.1.2.	Asbestos Removal Requirements.....	7
7.1.3.	OSHA Regulation of <1 Percent Asbestos	8
7.1.4.	State of Nebraska Asbestos Removal Regulations	8
7.2.	Lead-Based Paint.....	8
7.2.1.	Disposal Requirements	8
7.2.2.	Construction Requirements.....	8

APPENDIX A: Tables

APPENDIX B: Photo Logs

APPENDIX C: Analytical Results

APPENDIX D: Schematics

APPENDIX E: Inspectors' Credentials

HAZARDOUS MATERIALS INSPECTION REPORT

OFFUTT AFB PROJECT: SGBP 20-0041

Repair HVAC B 324 – Redesign

Offutt Air Force Base

Bellevue, Nebraska

November 22, 2022

1. SURVEY OVERVIEW

On October 31, 2022 Building 324, located on Offutt AFB, Bellevue, Nebraska, was inspected for asbestos-containing material (ACM) and lead-based paint (LBP) by representatives of AMI Environmental (AMIE). The inspection was conducted in preparation for renovation and/or repair of the building. The renovation and/or repair project is hereinafter referred to as “The Project”. The inspection was initiated at the request of Mr. Tom Svoboda, PE, CEM of Schemmer Associates.

The inspection was performed by Mr. Colin Lauenroth and Dustin Wessel of AMIE in accordance with regulatory requirements, and generally accepted industry methods. Copies of applicable requisite training certificates for Mr. Lauenroth and Mr. Wessel are provided in Appendix E.

1.1. Purpose and Scope

The purpose and scope of the inspection was to sample suspect ACMs and LBPs present in defined project area that may be impacted by The Project.

1.1.1. Inspection Area

The hazardous building materials inspection included all steam piping in B324 that will be impacted by the planned demolition/renovation activities including the basement mechanical room, 1st floor kitchen area, and the upper level mechanical space. The defined area for The Project is hereinafter referred to as the Inspection Area.

1.1.2. Limitations

At the discretion of the inspector(s), certain spaces may not have been inspected and/or samples not collected from materials that were not accessible at the time of the inspection. Examples of suspect materials that may not have been accessible include those which may exist inside finished interior walls and ceilings, and/or materials in areas not accessible due to locked doors, physical barriers, and/or safety, security, and related concerns. Materials requiring specialized equipment to access (e.g. lifts) are also considered not accessible unless prior arrangements were made. These materials, if present, should be identified at the time of renovation or demolition. Sampling of these materials may not be necessary if, in the case of suspect ACM, the materials are assumed to be ACM or if they are determined by a licensed asbestos inspector to be homogenous to other materials that were sampled.

1.2. Regulatory Reference

The asbestos inspection was conducted in accordance with USEPA National Emission Standard for Hazardous Air Pollutants (NESHAP) regulations (ref.: 40 CFR, Part 61), following criteria established for identifying asbestos-containing building materials that may be impacted by planned repair and renovation activities; applicable protocols established by the Asbestos Hazard Emergency Response Act (AHERA) (ref.: 40 CFR 763), and the State of Nebraska Department of Health and Human Services. There is also no licensing requirement for lead paint sampling in non-HUD facilities.

2. BUILDING INFORMATION

2.1. General Construction

Due to planned renovations, the steam piping in the building will no longer be required, and will be removed from the building.

2.2. Pre-Existing Information

No previous hazardous materials inspection and/or sampling information was available at the time of the inspection.

3. INSPECTION METHODOLOGIES

3.1. Asbestos Inspection

The asbestos inspection included visual identification and bulk sampling of suspect materials. The inspection and sampling were conducted in accordance with the USEPA National Emission Standard for Hazardous Air Pollutants (NESHAP) regulations (ref.: 40 CFR, Part 61), following criteria established for identifying asbestos-containing building materials that may be impacted by planned renovation. Additional aspects of the inspection methodology are discussed below.

3.1.1. Key Definitions

3.1.1.1. Homogenous Material

Homogenous materials are unique applications of building materials uniform in color and texture. The homogeneity of a material can be further defined by area(s) of application. Bulk sampling is conducted to determine the asbestos content of a homogenous material.

3.1.1.2. Asbestos-Containing Material (ACM)

The Environmental Protection Agency (EPA) and the Occupational Safety and Health Administration (OSHA) define ACMs as any material that contains greater than one percent asbestos, as determined by visual area estimation (microscopic analysis). The State of Kansas follows the EPA standard. Some materials contain one percent or less asbestos. While these materials are not ACMs by definition, they are still regulated by OSHA, but to a lesser degree.

3.1.1.3. Friable/Non-Friable ACM

Friable ACMs are materials that contain more than one percent asbestos and, when dry, can be crumbled, pulverized, or reduced to powder by hand pressure, thereby

releasing fibers into the air more readily. In contrast, non-friable ACMs are ACMs that, when dry, cannot be crumbled, pulverized, or reduced to powder by hand pressure. Non-friable ACMs are grouped into two categories: Category I and Category II.

3.1.1.4. Regulated Asbestos-Containing Materials (RACM)

Regulated Asbestos-Containing Materials (RACM) include friable ACMs and non-friable ACMs that, depending on their category, have become friable, have been subjected to specific forms of impact damage, have a high probability of becoming friable, and/or may become friable during removal.

3.1.2. *Homogenous Material Numbering Convention*

All suspect asbestos materials are assigned a unique homogeneous material number (HM#). The HM# begins with two or three letters, denoting the type of material, followed by a sequential number that is assigned to every material identified within each material type (example: ABC-01). The HM# is referenced throughout the report to uniquely identify each material. AHERA identifies three basic material types: Surfacing Materials (SM), which include spray and trowel applied materials, such as fireproofing, ceiling texture, plaster, etc.; Thermal System Insulation (TSI), which includes insulating materials applied to mechanical and plumbing components for temperature preservation and condensation prevention purposes; and Miscellaneous Materials (MM), which includes all other materials, such as floor coverings and mastics, roofing materials, asbestos cement products, and many others. When a homogenous material has multiple layers, individual layers are identified with a suffix, e.g. MM-03A, MM-03B, etc. A key defining acronyms is provided on the table(s).

3.1.3. *Bulk Sampling*

Bulk sampling must be performed to determine whether a certain homogenous material contains asbestos. Asbestos bulk sampling for the inspection was conducted in accordance with protocols established by the Asbestos Hazard Emergency Response Act (AHERA) (ref.: 40 CFR 763). All suspect homogenous materials and associated sampling of these materials are identified in *Table 1 – Asbestos Material Sampling Table*. Suspect materials not sampled are assumed to be ACM until properly sampled and determined otherwise. Some suspect materials, such as lab table tops, roofing systems, TSI, etc., may not be sampled to preclude damage. Friability of the suspect asbestos-containing materials was determined by touching and/or sampling of the material.

3.1.3.1. Bulk Sample Numbering Convention

Bulk samples are given a sequence number when collected. When sampling information from multiple surveys are incorporated into the same report, which may result in duplicate sample numbers, the sample numbers in the *Asbestos Material Sampling Table* differentiate prior sampling events by including the year in which the previous sample was collected as a prefix to the sample number. For example, a sample number of 1993-46A denotes sample no. 46A from a 1993 survey. This report contains no sampling information from previous surveys in the inspection area.

3.1.3.2. Polarized Light Microscopy Analysis (PLM)

Bulk samples collected during the inspection were submitted to an EPA accredited laboratory, EMSL Analytical, Inc. (EMSL), located at 6340 CastlePlace Dr.

Indianapolis, IN 46250. EMSL was instructed to perform Polarized Light Microscopy (PLM) analysis, utilizing dispersion staining techniques (ref: EPA Method 600/M4-82-020). PLM analysis is the least expensive and most commonly used visual estimate method. While PLM analysis is acceptable to EPA, OSHA, and most states for determining asbestos content, some states now require more sophisticated methods when analyzing certain types of materials.

A total of thirty-one (31) asbestos bulk samples were collected and submitted for laboratory analysis from homogenous materials identified during the asbestos inspection. PLM analysis was performed on a total of forty-four (44) heterogeneous applications identified in the homogenous materials. Heterogeneous applications are individual layers of different materials contained within a single bulk sample, each of which must be analyzed individually to determine its asbestos content (e.g. vinyl floor tiles and mastic; cove base and mastic; etc.).

Some samples and/or heterogeneous applications may not have been analyzed by the lab if a positive result was obtained from a sample that is among a group of samples representing a suspect material. This process, known as “stop on first positive,” is followed because if a single sample is found to be positive, that material is determined to be ACM, thus making it unnecessary to analyze any additional samples in the sampling group.

Please refer to the *Table 1 – Asbestos Material Sampling Table* in Appendix A for a complete listing of all materials sampled. The laboratory analytical reports may be found in Appendix C.

3.1.3.3. Quantification Method Analysis

EPA regulations allow materials determined to contain less than 10 percent asbestos utilizing a visual estimate quantification method, such as PLM analysis, to be treated as non-asbestos containing if the material is re-analyzed using one of two quantification methods and determined to contain one percent or less of asbestos. The two acceptable quantification methods are point count analysis and TEM Chatfield analysis.

Quantification methods are more time-consuming and more expensive analytical procedures that are occasionally used to more accurately determine the amount of asbestos in certain samples. Because of their higher cost and the acceptable accuracy of the less expensive visual estimation method, laboratories do not typically perform quantification analyses unless specifically requested.

The quantification method known as point count analysis is used for most ACM types, except floor tile. The organic matrix composition of floor tile precludes the use of point count analysis to more accurately determine asbestos amounts within a sample. Therefore, TEM Chatfield analysis—which effectively removes all organic materials, leaving only asbestos behind—is necessary to provide a more precise percentage of asbestos content in floor tile.

Please refer to section *6.0 Recommendations*, for recommendations concerning supplemental analysis.

3.2. Lead-Based Paint Inspection

The LBP inspection included visual identification of homogenous paint applications and bulk (chip) sampling of the paint(s). While the U. S. Department of Housing and Urban Development (HUD)

promulgates guidelines for LBP inspections in child occupied facilities, there are no formal guidelines for non-HUD regulated inspections. Thus, the LBP inspection was conducted in accordance with generally accepted industry standards and practices. Additional aspects of the inspection methodology are discussed below.

3.2.1. Key Definitions

3.2.1.1. Homogenous Paint Applications

Homogenous paint applications are significant paint applications that are visually distinct by their color and uniformity. Significant paint applications do not include incidental occurrences of paint such as isolated occurrences of accent trim, artistic paints, etc. While visual inspection alone cannot generally identify sub-layers of paint, these applications are often identified during the chip sampling process.

3.2.1.2. Lead-Based Paint (LBP)

Pursuant to Federal Register, Vol. 61, No. 169, LBP is defined as paint or other surface coatings containing more than 0.5 percent lead by weight.

3.2.2. Homogenous Paint Applications Numbering Convention

Homogenous paints and coatings are assigned a unique homogeneous material number (HM#). For paints, the HM# begins with “L”, followed by a sequential number that is assigned to every paint identified (e.g. L-1). The HM# is referenced throughout the report to uniquely identify each paint application.

3.2.3. Lead-based Paint and Lead-containing Material Sampling

A total of two (2) homogeneous painted materials were collected from significant and visually distinct paint applications identified during the lead paint inspection. Additionally, one (1) ceramic tile flooring was sampled as suspect lead-containing material. The samples were submitted to EMSL for laboratory analysis, utilizing Flame Atomic Absorption Spectrophotometry (SW 846 3050B/7000B). EMSL’s NLLAP (National Lead Laboratory Accreditation Program) and AIHA ELLAP (Environmental Lead Laboratory Accreditation Program) accreditation number is 157245.

Please refer to *Table 2 – Lead Paint Sampling Table* in Appendix A for a complete listing of the paint applications identified and sampled for lead. The laboratory’s analytical reports are provided in Appendix C.

4. SUMMARY OF INSPECTION FINDINGS

Key findings of the hazardous building materials inspection are summarized below. Please refer to the Appendices for complete details of the inspection findings and supporting documentation.

4.1. Asbestos Inspection Findings

• Mudded Fittings (Gray/White)	4% Chrysotile	3 EA
• Mudded Fittings (White)	10% Chrysotile/5% Amosite	12 EA
• Mudded Fittings (Brown/White)	2% Chrysotile	6 EA
• Mudded Fittings (Gray)	5% Chrysotile	30 EA
• Tank Insulation (Gray)	15% Chrysotile	225 SF

4.2. Lead-Based Paint Inspection Findings

- Concrete Pad Edge Paint 2.7% Lead by Weight 70 SF
- Paint applications were determined to contain detectable levels of lead. See Section 7.2 for more information on Lead in Construction.

See Appendix D, Schematics, for locations of Asbestos Containing Materials and Lead-Based Paint.

5. RISKS AND HAZARDS

5.1. Asbestos

To be a significant health concern, asbestos fibers must be inhaled. When asbestos fibers are inhaled, they become lodged in the lung tissue or alveoli. Here they clog and scar the tissues, causing the walls of the alveoli to lose their elasticity and useful function in respiration. Asbestosis (scarring of the lung), lung cancer, and Mesothelioma (cancer of the lining of the chest or lining of the abdominal wall) are diseases associated with asbestos exposure. Risks and hazards increase with increased exposure. ACM condition, proximity to building occupants, building use, and other factors can influence the potential for asbestos fibers to become airborne, and therefore increase exposure risks.

5.2. Lead-Based Paint

Inhalation and ingestion are the major routes of lead exposure. Once in the body, lead is distributed via the bloodstream to red blood cells, soft-tissue and bone. The kidneys and gastrointestinal (GI) tract eliminate lead in the body very slowly, while minute amounts are lost through perspiration.

Lead in the body can cause serious damage to the central and peripheral nervous system, the cardiovascular system, and the kidneys. Exposure to high concentrations of lead can cause retardation, convulsions, coma, and sometimes death. Children are especially vulnerable and susceptible to lead poisoning. Even low levels of exposure persisting during childhood are known to slow a child's normal development and cause learning and behavioral problems. Exposure to lead can result from deteriorating surfaces and activities mechanically impacting lead surfaces. Preventing exposure requires proper work practices, monitoring, disposal and personal protective equipment during demolition, alteration and friction producing activities.

6. RECOMMENDATIONS

The purpose of this section is to interpret survey findings and provide preliminary recommendations that may be relevant and appropriate at this time. Because this document is a presentation of investigative findings, recommendations related to future construction activities are inherently general in nature. More specific determinations concerning hazardous building materials to be impacted by construction should be made during the abatement project design process.

6.1. General Recommendations

6.1.1. Asbestos

State and/or federal regulations require that ACMs be removed prior to demolition or renovation activities that will impact the ACMs. Depending on the specific renovation work to be performed, certain ACMs, may not require removal if they will not be disturbed and do not pose a risk to building occupants or construction trade workers. However, to ensure worker safety and to eliminate future asbestos-related maintenance and

management costs and risks, AMIE recommends removal of all identified ACMs in the areas to be renovated.

6.1.2. Lead-Based Paint

Facility owners are ultimately liable for their lead-containing hazardous waste from cradle to grave. EPA regulations provide two ways to determine whether a waste stream, such as demolition debris containing LBP, must be classified as hazardous waste. Waste generators can either test the waste using an approved testing method (Toxicity Characteristic Leaching Procedure [TCLP]), or they can apply knowledge of the hazardous characteristic of the waste.

AMIE recommends TCLP testing be conducted on the existing building materials, painted and unpainted, prior to the start of renovation or demolition activity to document that the waste stream is acceptable for disposal of as non-hazardous waste. In addition, trade contractors who work in the facility should be notified of the presence of paints containing lead so that they can appropriately monitor and protect their workers against lead exposure.

6.2. Hazardous Conditions Recommendations

Potentially hazardous conditions were observed in the building and are described below. The conditions described are not intended to be a complete assessment of potential hazards. Additional hazards may be present.

- No immediately hazardous conditions were observed.

6.3. Point Count Analysis / TEM Chatfield Analysis Recommendations

No additional laboratory analysis is recommended.

7. REGULATORY REQUIREMENTS

7.1. Asbestos-Containing Materials

The removal and disposal of ACMs is regulated at the federal, state, and, sometimes, local level. While some states have developed their own regulatory standards for the various asbestos disciplines, many states have adopted the federal standards but have established licensing requirements and enforcement authority at the state level.

7.1.1. Notification Requirements

EPA's NESHAP regulation, 40 CFR, Subpart M, 61.145, Standard for Demolition and Renovation, stipulates that an owner of a facility submit proper notification with either the EPA's regional office and/or the state and local regulatory agency of intention to demolish or renovate. Notifications must be received by the appropriate regulatory agencies 10 working days prior to commencement of asbestos stripping or removal, or other site work. If the demolition or renovation date changes, or the scope of work is increased by more than 20 percent, another notification must be made.

7.1.2. Asbestos Removal Requirements

Asbestos removal must be performed by a licensed abatement contractor. The contractor should follow all work practices, worker protection, and disposal requirements set forth in the contract specifications and by the Occupational Safety and Health Administration

(OSHA) and the EPA. Key federal regulations concerning asbestos include 29 CFR 1910.1001, 29 CFR 1926.1101, 40 CFR Part 61, Subpart M, and 40 CFR 763.

7.1.3. OSHA Regulation of <1 Percent Asbestos

While EPA and many states do not regulate materials containing less than one percent asbestos, OSHA regulates materials containing any amount of asbestos. (Ref. OSHA Construction Industry Standard, 29 CFR 1926.1101(a)(3))

7.1.4. State of Nebraska Asbestos Removal Regulations

State of Nebraska regulates the removal of friable asbestos-containing materials and non-friable asbestos containing materials that may become friable during removal, when affected quantities are greater than three square or three linear feet. For a complete understanding of the Nebraska governing asbestos projects, refer to Title 178, Chapter 22.

7.2. Lead-Based Paint

7.2.1. Disposal Requirements

The Resource Conservation and Recovery Act (RCRA) classifies lead-containing waste streams as hazardous materials if TCLP levels exceed five parts per million. If TCLP leachable lead levels exceed that threshold, EPA regulations (40 CFR 261) require the waste stream to be handled and disposed of as a hazardous waste. Waste streams containing less the five parts per million of leachable lead are classified as non-hazardous waste and can be disposed of in a construction and demolition landfill.

7.2.2. Construction Requirements

OSHA's 29 CFR 1926.62 regulates worker exposure to lead during construction activities that include demolition or salvage of structures where lead or materials containing lead are present, as well as removal or encapsulation of lead-containing materials. The standard establishes maximum limits of exposure to lead, including a permissible exposure limit and action level, and should be adhered to during construction and demolition activities.

APPENDIX A

Table 1 – Asbestos Sampling

Table 2 – Lead-based Paint Sampling

Table 1

Material #/ Description	Sample ID	Layer ID	Color	Location	Sample Result	Condition	Friable (Y/N)	Estimated Quantity	Photo No.
TSI-01: Fiberglass Pipe Wrap w/ Mastic (White) 2" Pipe	01 02 03	01 02 03 - Wrap	White/ Silver	Kitchen pipes and Attic (HPS, LPS, Condensate)	Non-Detect				1
TSI-01A: Fiberglass Pipe Wrap w/ Mastic (White) 2" Pipe	01 02 03	01 02 03 - Mastic	White	Kitchen pipes and Attic (HPS, LPS, Condensate)	Non-Detect				1
TSI-02: Fiberglass Pipe Wrap w/ Mastic (White) 4" Pipe	04 05 06	04 05 06 - Wrap	White/ Silver	Kitchen pipes and Attic pipes	Non-Detect				2
TSI-02A: Fiberglass Pipe Wrap w/ Mastic (White) 4" Pipe	04 05 06	04 05 06 -Mastic	Yellow/ White	Kitchen pipes and Attic pipes	Non-Detect				2
TSI-03: Large Mudded Fitting (Gray/White) 2' Fitting	07 08 09	07 08 09 -Mudded Fitting	Gray	Basement Southeast Corner	4% Chrysotile	Good	Y	3 EA	3
TSI-03A: Large Mudded Fitting (Gray/White) 2' Fitting	07 08 09	07 08 09 -Wrap	Tan/ White	Basement Southeast Corner	Non-Detect				3
TSI-04: 4" Mudded Fittings (White)	10 11 12	10 11 12 -Mudded Fitting	White	Basement South Side	5% Amosite 10% Chrysotile	Fair	Y	12 EA	4
TSI-04A: 4" Mudded Fittings (White)	10 11 12	10 11 12 -Wrap	White/ Tan	Basement South Side	Non-Detect				4
TSI-05: 4" Mudded Fittings (Brown/White)	13 14 15	13 14 15 -Mudded Fitting	Gray	Basement, South side above other pipes	2% Chrysotile	Fair	Y	6 EA	5

Table 1: Asbestos-Containing Material Sampling Table & Test Results

AMI Project No.: 22-275

Offutt AFB Dining Hall B-324

November 22, 2022



Table 1

Material #/ Description	Sample ID	Layer ID	Color	Location	Sample Result	Condition	Friable (Y/N)	Estimated Quantity	Photo No.
TSI-05A: 4" Mudded Fittings (Brown/White)	13 14 15	13 14 15 -Wrap	White	Basement, South side above other pipes	Non-Detect				5
TSI-06: 6" Mudded Fittings (Gray)	16 17 18	16 17 18 -Mudded Fitting	Gray	Basement, North side and center	5% Chrysotile	Fair	Y	30 EA	6
TSI-06A: 6" Mudded Fittings (Gray)	16 17 18	16 17 18 -Wrap	White	Basement, North side and center	Non-Detect				6
TSI-07: Insulation (Expansion Tank)	19 20 21	19 20 21	Gray	Basement north side	15% Chrysotile	Poor	Y	225 SF	7
TSI-08: Interior Boiler Insulation (Gray/Tan)	22 23	22 23 -Filler	Gray/Tan	Boilers on West side of basement	<1% Chrysotile				8
TSI-08A: Interior Boiler Insulation (Gray/Tan)	22 23	22 23 -Insulation	Gray/Tan	Boilers on West side of basement	Non-Detect				8
TSI-09: 12" Fiberglass Pipe Insulation (HPS) w/ Mastic (White)	24 25 26	24 25 26 -Insulation	Tan	Basement center	Non-Detect				9
TSI-09A: 12" Fiberglass Pipe Insulation (HPS) w/ Mastic (White)	24 25 26	24 25 26 -Mastic	Tan/ White	Basement center	Non-Detect				9
MM-01: Gasket (Black)	27 28	27 28	Black	Deaerator Tank	Non-Detect				10
TSI-10: Tank Wrap (White/Tan)	29 30 31	29 30 31	Tan/ White/ Rust	Deaerator Tank	Non-Detect				11

Table 1: Asbestos-Containing Material Sampling Table & Test Results

AMI Project No.: 22-275

Offutt AFB Dining Hall B-324

November 22, 2022



Table 2

Sample	Location	Description	Substrate	Color	Paint Condition	Lab Result (% by Weight)	Estimated Quantity	Photo No.
L-1	Basement north side Condensate Tank	Condensate Tank	Metal	White	Poor	0.042 % wt		1
L-2	Basement throughout. Concrete pad edges	Concrete Pad	Concrete	Yellow Green	Poor	2.7 % wt	70 SF	2

Table 2: Lead Based Paint Sampling Table & Test Results
 AMI Project No.: 22-275
 Offutt AFB Dining Hall B-324
 November 22, 2022



APPENDIX B

Photo Logs

Asbestos Photo Log

Lead-Based Paint Photo Log

www.amienvironmental.com

8802 South 135th Street, Suite 100 • Omaha, NE 68138
800.828.8487 • 402.397.5001 • 402.397.3313 (fax)



PHOTO 1 TSI-01: Fiberglass Pipe Wrap w/ Mastic (White) 2" Pipe



PHOTO 2 TSI-02: Fiberglass Pipe Wrap w/ Mastic (White) 4" Pipe




PHOTO 3 TSI-03: Large Mudded Fitting (4% Chrysotile), and non-ACM wrap.



PHOTO 4 TSI-04: 4" Mudded Fittings (White) (5% Amosite and 10% Chrysotile) and non-ACM wrap.




PHOTO 5 TSI-05: 4" Mudded Fittings (Brown/White) (2% Chrysotile) and non-ACM wrap.




PHOTO 6 TSI-06: 6" Mudded Fittings (Gray) (5% Chrysotile) and non-ACM wrap.




PHOTO 7 **TSI-07: Insulation (Expansion Tanks) (15% Chrysotile).**




PHOTO 8 **TSI-08 Interior Boiler Insulation and filler (<1% Chrysotile).**




PHOTO 9 **TSI-09: 12" Fiberglass Pipe Insulation (HPS) w/ Mastic (White)**



PHOTO 10 **MM-01: Gasket, Black.**




PHOTO 11 **TSI-10: Tank Wrap (White/Tan)**



PHOTO 1

White on metal Condensate Tank.




PHOTO 2

Yellow and Green on Concrete Pad. 2.7% lead by weight.

APPENDIX C

Laboratory Results



EMSL Analytical, Inc.

6340 CastlePlace Dr. Indianapolis, IN 46250

Tel/Fax: (317) 803-2997 / (317) 803-3047

<http://www.EMSL.com> / indianapolislabs@emsl.com

EMSL Order: 162225586

Customer ID: AMI50

Customer PO:

Project ID:

Attention: Colin Lauenroth

AMI Group, Inc.

8802 South 135th Street

Suite 100

Omaha, NE 68138-6511

Project: 22-275 Offutt AFB Dining Hall ACM

Phone: (402) 397-5001

Fax: (402) 397-3313

Received Date: 11/01/2022 9:50 AM

Analysis Date: 11/01/2022 - 11/02/2022

Collected Date: 10/31/2022

Test Report: Asbestos Analysis of Bulk Materials via EPA 600/R-93/116 Method using Polarized Light Microscopy

Sample	Description	Appearance	Non-Asbestos		Asbestos
			% Fibrous	% Non-Fibrous	% Type
01-Wrap 162225586-0001	Fiberglass Pipe Wrap w/Mastic(White) 2" Pipe - Kitchen Pipes + Attic(HPS, LPS, Condensate)	White/Silver Fibrous Homogeneous	70% Cellulose 10% Glass	20% Non-fibrous (Other)	None Detected
01-Mastic 162225586-0001A	Fiberglass Pipe Wrap w/Mastic(White) 2" Pipe - Kitchen Pipes + Attic(HPS, LPS, Condensate)	White Non-Fibrous Homogeneous		100% Non-fibrous (Other)	None Detected
02-Wrap 162225586-0002	Fiberglass Pipe Wrap w/Mastic(White) 2" Pipe - Kitchen Pipes + Attic(HPS, LPS, Condensate)	White/Silver Fibrous Homogeneous	70% Cellulose 10% Min. Wool	20% Non-fibrous (Other)	None Detected
02-Mastic 162225586-0002A	Fiberglass Pipe Wrap w/Mastic(White) 2" Pipe - Kitchen Pipes + Attic(HPS, LPS, Condensate)	White Non-Fibrous Homogeneous		100% Non-fibrous (Other)	None Detected
03-Wrap 162225586-0003	Fiberglass Pipe Wrap w/Mastic(White) 2" Pipe - Kitchen Pipes + Attic(HPS, LPS, Condensate)	White/Silver Fibrous Homogeneous	70% Cellulose 10% Glass	20% Non-fibrous (Other)	None Detected
03-Mastic 162225586-0003A	Fiberglass Pipe Wrap w/Mastic(White) 2" Pipe - Kitchen Pipes + Attic(HPS, LPS, Condensate)	White Non-Fibrous Homogeneous		100% Non-fibrous (Other)	None Detected
04-Wrap 162225586-0004	Fiberglass Pipe Wrap w/Mastic(White) 4" Pipe - Kitchen Pipes + Attic Pipes	White/Silver Fibrous Homogeneous	70% Cellulose 15% Min. Wool	15% Non-fibrous (Other)	None Detected
04-Mastic 162225586-0004A	Fiberglass Pipe Wrap w/Mastic(White) 4" Pipe - Kitchen Pipes + Attic Pipes	Yellow Non-Fibrous Homogeneous		100% Non-fibrous (Other)	None Detected
05-Wrap 162225586-0005	Fiberglass Pipe Wrap w/Mastic(White) 4" Pipe - Kitchen Pipes + Attic Pipes	White/Silver Fibrous Homogeneous	65% Cellulose 20% Glass	15% Non-fibrous (Other)	None Detected
05-Mastic 162225586-0005A	Fiberglass Pipe Wrap w/Mastic(White) 4" Pipe - Kitchen Pipes + Attic Pipes	Yellow Non-Fibrous Homogeneous		100% Non-fibrous (Other)	None Detected
06-Wrap 162225586-0006	Fiberglass Pipe Wrap w/Mastic(White) 4" Pipe - Kitchen Pipes + Attic Pipes	White/Silver Fibrous Homogeneous	50% Cellulose 20% Glass	30% Non-fibrous (Other)	None Detected

Initial report from: 11/02/2022 16:01:52



EMSL Analytical, Inc.

6340 CastlePlace Dr. Indianapolis, IN 46250

Tel/Fax: (317) 803-2997 / (317) 803-3047

<http://www.EMSL.com> / indianapolislabs@emsl.com

EMSL Order: 162225586

Customer ID: AMI50

Customer PO:

Project ID:

Test Report: Asbestos Analysis of Bulk Materials via EPA 600/R-93/116 Method using Polarized Light Microscopy

Sample	Description	Appearance	Non-Asbestos		Asbestos
			% Fibrous	% Non-Fibrous	% Type
06-Mastic 162225586-0006A	Fiberglass Pipe Wrap w/Mastic(White) 4" Pipe - Kitchen Pipes + Attic Pipes	Yellow Non-Fibrous Homogeneous		100% Non-fibrous (Other)	None Detected
07-Mudded Fitting 162225586-0007	Large Mudded Fitting(Gray/White) 2' Fitting - Basement South-East Corner	Gray Fibrous Homogeneous	30% Min. Wool	66% Non-fibrous (Other)	4% Chrysotile
07-Wrap 162225586-0007A	Large Mudded Fitting(Gray/White) 2' Fitting - Basement South-East Corner	Tan/White Fibrous Homogeneous	90% Cellulose	10% Non-fibrous (Other)	None Detected
08-Mudded Fitting 162225586-0008	Large Mudded Fitting(Gray/White) 2' Fitting - Basement South-East Corner				Positive Stop (Not Analyzed)
08-Wrap 162225586-0008A	Large Mudded Fitting(Gray/White) 2' Fitting - Basement South-East Corner	White Fibrous Homogeneous	98% Cellulose	2% Non-fibrous (Other)	None Detected
09-Mudded Fitting 162225586-0009	Large Mudded Fitting(Gray/White) 2' Fitting - Basement South-East Corner				Positive Stop (Not Analyzed)
09-Wrap 162225586-0009A	Large Mudded Fitting(Gray/White) 2' Fitting - Basement South-East Corner	White Fibrous Homogeneous	98% Cellulose	2% Non-fibrous (Other)	None Detected
10-Mudded Fitting 162225586-0010	4" Mudded Fittings(White) - Basement South Side	White Fibrous Homogeneous	30% Min. Wool	55% Non-fibrous (Other)	5% Amosite 10% Chrysotile
10-Wrap 162225586-0010A	4" Mudded Fittings(White) - Basement South Side	Gray/White Fibrous Homogeneous	95% Cellulose	5% Non-fibrous (Other)	None Detected
11-Mudded Fitting 162225586-0011	4" Mudded Fittings(White) - Basement South Side				Positive Stop (Not Analyzed)
11-Wrap 162225586-0011A	4" Mudded Fittings(White) - Basement South Side	White Fibrous Homogeneous	98% Cellulose	2% Non-fibrous (Other)	None Detected
12-Mudded Fitting 162225586-0012	4" Mudded Fittings(White) - Basement South Side				Positive Stop (Not Analyzed)
12-Wrap 162225586-0012A	4" Mudded Fittings(White) - Basement South Side	Tan Fibrous Homogeneous	95% Cellulose	5% Non-fibrous (Other)	None Detected
13-Mudded Fitting 162225586-0013	4" Mudded Fittings (Brown/White) - Basement, South Side Above Other Pipes	Gray Fibrous Homogeneous	40% Min. Wool	58% Non-fibrous (Other)	2% Chrysotile
13-Wrap 162225586-0013A	4" Mudded Fittings (Brown/White) - Basement, South Side Above Other Pipes	White Fibrous Homogeneous	95% Cellulose	5% Non-fibrous (Other)	None Detected

Initial report from: 11/02/2022 16:01:52



EMSL Analytical, Inc.

6340 CastlePlace Dr. Indianapolis, IN 46250

Tel/Fax: (317) 803-2997 / (317) 803-3047

<http://www.EMSL.com> / indianapolislabs@emsl.com

EMSL Order: 162225586

Customer ID: AMI50

Customer PO:

Project ID:

Test Report: Asbestos Analysis of Bulk Materials via EPA 600/R-93/116 Method using Polarized Light Microscopy

Sample	Description	Appearance	Non-Asbestos		Asbestos
			% Fibrous	% Non-Fibrous	% Type
14-Mudded Fittings 162225586-0014	4" Mudded Fittings (Brown/White) - Basement, South Side Above Other Pipes				Positive Stop (Not Analyzed)
14-Wrap 162225586-0014A	4" Mudded Fittings (Brown/White) - Basement, South Side Above Other Pipes	White Fibrous Homogeneous	95% Cellulose	5% Non-fibrous (Other)	None Detected
15-Mudded Fittings 162225586-0015	4" Mudded Fittings (Brown/White) - Basement, South Side Above Other Pipes				Positive Stop (Not Analyzed)
15-Wrap 162225586-0015A	4" Mudded Fittings (Brown/White) - Basement, South Side Above Other Pipes	White Fibrous Homogeneous	95% Cellulose	5% Non-fibrous (Other)	None Detected
16-Mudded Fitting 162225586-0016	6" Mudded Fittings(Gray) - Basement, North Side and Center	Gray Fibrous Homogeneous	50% Min. Wool	45% Non-fibrous (Other)	5% Chrysotile
16-Wrap 162225586-0016A	6" Mudded Fittings(Gray) - Basement, North Side and Center	White Fibrous Homogeneous	95% Cellulose	5% Non-fibrous (Other)	None Detected
17-Mudded Fitting 162225586-0017	6" Mudded Fittings(Gray) - Basement, North Side and Center				Positive Stop (Not Analyzed)
17-Wrap 162225586-0017A	6" Mudded Fittings(Gray) - Basement, North Side and Center	White Fibrous Homogeneous	95% Cellulose	5% Non-fibrous (Other)	None Detected
18-Mudded Fitting 162225586-0018	6" Mudded Fittings(Gray) - Basement, North Side and Center				Positive Stop (Not Analyzed)
18-Wrap 162225586-0018A	6" Mudded Fittings(Gray) - Basement, North Side and Center	White Fibrous Homogeneous	95% Cellulose	5% Non-fibrous (Other)	None Detected
19 162225586-0019	Insulation(Expansion Tank) - Basement, North Side	Gray Fibrous Homogeneous	50% Min. Wool	35% Non-fibrous (Other)	15% Chrysotile
20 162225586-0020	Insulation(Expansion Tank) - Basement, North Side				Positive Stop (Not Analyzed)
21 162225586-0021	Insulation(Expansion Tank) - Basement, North Side				Positive Stop (Not Analyzed)
22-Filler 162225586-0022	Interior Boiler Insulation(Gray/Tan) - Boilers on West Side of Basement	Gray/Tan Non-Fibrous Homogeneous		100% Non-fibrous (Other)	<1% Chrysotile

Initial report from: 11/02/2022 16:01:52



EMSL Analytical, Inc.

6340 CastlePlace Dr. Indianapolis, IN 46250

Tel/Fax: (317) 803-2997 / (317) 803-3047

<http://www.EMSL.com> / indianapolislaboratory@emsl.com

EMSL Order: 162225586

Customer ID: AMI50

Customer PO:

Project ID:

Test Report: Asbestos Analysis of Bulk Materials via EPA 600/R-93/116 Method using Polarized Light Microscopy

Sample	Description	Appearance	Non-Asbestos		Asbestos
			% Fibrous	% Non-Fibrous	% Type
22-Insulation 162225586-0022A	Interior Boiler Insulation(Gray/Tan) - Boilers on West Side of Basement	Tan Fibrous Homogeneous	95% Min. Wool	5% Non-fibrous (Other)	None Detected
23-Filler 162225586-0023	Interior Boiler Insulation(Gray/Tan) - Boilers on West Side of Basement	Gray/Tan Non-Fibrous Homogeneous		100% Non-fibrous (Other)	<1% Chrysotile
23-Insulation 162225586-0023A	Interior Boiler Insulation(Gray/Tan) - Boilers on West Side of Basement	Gray/Tan Fibrous Homogeneous	95% Min. Wool	5% Non-fibrous (Other)	None Detected
24-Insulation 162225586-0024	12" Fiberglass Pipe Insulation(HPS) w/Mastic(White) - Basement Center	Tan Fibrous Homogeneous	98% Glass	2% Non-fibrous (Other)	None Detected
24-Mastic 162225586-0024A	12" Fiberglass Pipe Insulation(HPS) w/Mastic(White) - Basement Center	Tan/White Non-Fibrous Homogeneous		100% Non-fibrous (Other)	None Detected
25-Insulation 162225586-0025	12" Fiberglass Pipe Insulation(HPS) w/Mastic(White) - Basement Center	Tan Fibrous Homogeneous	98% Glass	2% Non-fibrous (Other)	None Detected
25-Mastic 162225586-0025A	12" Fiberglass Pipe Insulation(HPS) w/Mastic(White) - Basement Center	Tan/White Non-Fibrous Homogeneous		100% Non-fibrous (Other)	None Detected
26-Insulation 162225586-0026	12" Fiberglass Pipe Insulation(HPS) w/Mastic(White) - Basement Center	Tan Fibrous Homogeneous	98% Glass	2% Non-fibrous (Other)	None Detected
26-Mastic 162225586-0026A	12" Fiberglass Pipe Insulation(HPS) w/Mastic(White) - Basement Center	Tan/White Non-Fibrous Homogeneous		100% Non-fibrous (Other)	None Detected
27 162225586-0027	Gasket(Black) - Deaerator Tank	Black Non-Fibrous Homogeneous		100% Non-fibrous (Other)	None Detected
28 162225586-0028	Gasket(Black) - Deaerator Tank	Black Non-Fibrous Homogeneous		100% Non-fibrous (Other)	None Detected
29 162225586-0029	Tank Wrap(White/Tan) - Deaerator Tank	Tan/White Fibrous Homogeneous	80% Cellulose 5% Glass	15% Non-fibrous (Other)	None Detected
30 162225586-0030	Tank Wrap(White/Tan) - Deaerator Tank	White/Rust Fibrous Homogeneous	70% Cellulose 20% Glass	10% Non-fibrous (Other)	None Detected
31 162225586-0031	Tank Wrap(White/Tan) - Deaerator Tank	White/Rust Fibrous Homogeneous	50% Cellulose 20% Glass	30% Non-fibrous (Other)	None Detected

Initial report from: 11/02/2022 16:01:52



EMSL Analytical, Inc.

6340 CastlePlace Dr. Indianapolis, IN 46250

Tel/Fax: (317) 803-2997 / (317) 803-3047

<http://www.EMSL.com> / indianapolislaboratory@emsl.com

EMSL Order: 162225586

Customer ID: AMI50

Customer PO:

Project ID:

Analyst(s)

Alison Pacey (30)

Ross Matlock (14)

Asbestos Laboratory Manager
or Other Approved Signatory

EMSL maintains liability limited to cost of analysis. Interpretation and use of test results are the responsibility of the client. This report relates only to the samples reported above, and may not be reproduced, except in full, without written approval by EMSL. EMSL bears no responsibility for sample collection activities or analytical method limitations. The report reflects the samples as received. Results are generated from the field sampling data (sampling volumes and areas, locations, etc.) provided by the client on the Chain of Custody. Samples are within quality control criteria and met method specifications unless otherwise noted. The above analyses were performed in general compliance with Appendix E to Subpart E of 40 CFR (previously EPA 600/M4-82-020 "Interim Method") but augmented with procedures outlined in the 1993 ("final") version of the method. This report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST or any agency of the federal government. Non-friable organically bound materials present a problem matrix and therefore EMSL recommends gravimetric reduction prior to analysis. Unless requested by the client, building materials manufactured with multiple layers (i.e. linoleum, wallboard, etc.) are reported as a single sample. Estimation of uncertainty is available on request.

Samples analyzed by EMSL Analytical, Inc. Indianapolis, IN NVLAP Lab Code 200188-0, AZ0939, CA 2575, CO AL-15132, TX 300262

Initial report from: 11/02/2022 16:01:52

**EMSL Analytical, Inc.**

6340 CastlePlace Dr., Indianapolis, IN 46250

Phone/Fax: (317) 803-2997 / (317) 803-3047

<http://www.EMSL.com>indianapolislab@emsl.com

EMSL Order: 162225523

CustomerID: AMI50

CustomerPO: 22-275

ProjectID:

Attn: **Colin Lauenroth**
AMI Group, Inc.
8802 South 135th Street
Suite 100
Omaha, NE 68138-6511

Phone: (402) 397-5001
Fax: (402) 397-3313
Received: 11/1/2022 09:50 AM
Collected: 10/31/2022

Project: **22-275, OFFUTT AFB DINING HALL LBP, OFFUTT AFB, NEBRASKA****Test Report: Lead in Paint Chips by Flame AAS (SW 846 3050B/7000B)***

<i>Client Sample Description</i>	<i>Collected</i>	<i>Analyzed</i>	<i>Weight</i>	<i>RDL</i>	<i>Lead Concentration</i>
L-1 162225523-0001	10/31/2022	11/1/2022	0.2542 g	0.0080 % wt	0.042 % wt
Site: BASEMENT, N SIDE, CONDENSATE TANK PAINT (METAL), WHITE					
L-2 162225523-0002	10/31/2022	11/1/2022	0.2595 g	0.080 % wt	2.7 % wt
Site: BASEMENT, THROUGHOUT (EDGES OF PADS), CONCRETE PAD PAINT, YELLOW GREEN					

Aleksandra Kuchenbrod, Inorganic Chemistry
Lab Manager
or other approved signatory

EMSL maintains liability limited to cost of analysis. Interpretation and use of test results are the responsibility of the client. This report relates only to the samples reported above, and may not be reproduced, except in full, without written approval by EMSL. EMSL bears no responsibility for sample collection activities or analytical method limitations. The report reflects the samples as received. Results are generated from the field sampling data (sampling volumes and areas, locations, etc.) provided by the client on the Chain of Custody. Samples are within quality control criteria and met method specifications unless otherwise noted.


* Analysis following Lead in Paint by EMSL SOP/Determination of Environmental Lead by FLAA. Reporting limit is 0.008% wt based on the minimum sample weight per our SOP. "<" (less than) result signifies the analyte was not detected at or above the reporting limit. Measurement of uncertainty is available upon request. Definitions of modifications are available upon request.

Samples analyzed by EMSL Analytical, Inc. Indianapolis, IN AIHA-LAP, LLC-ELLAP 157245, OH E10040

Initial report from 11/02/2022 07:48:40

APPENDIX E

Inspector Credentials



Midwest Training Institute

"A Higher Standard of Training"

An **ATC** Company

This is to certify that

Colin Savenroth

has completed the requisite training for asbestos accreditation under TSCA Title II, 15 U.S.C. 2646 and the State of Nebraska Asbestos Regulations and passed the associated examination with a score of 70% or better.

EPA AHERA/Nebraska Asbestos Inspector Refresher Course

Midwest Training Institute, Inc.

10731 Mockingbird Drive

Omaha, NE 68127

(402) 505-2940

(402) 515-0585

www.midwesttrainingsite.com

Course Location:

Omaha, NE

Course Date: 06/28/2022

Examination Date: 06/28/2022

Expiration Date: 06/28/2023

Certificate # MTITB 01125

Course Length – 4 Hours

Todd B...

Instructor

State of Nebraska

Department of Health and Human Services

Division of Public Health

Colin J Lauenroth


Asbestos Inspector

License #: 1402

Status: Active

Expiration: 09/15/2024





Midwest Training Institute

"A Higher Standard of Training"

An **ATC** Company

This certifies that

Dustin Wessel

has completed the requisite training for asbestos accreditation under TSCA Title II, 15 U.S.C. 2646 and the State of Nebraska Asbestos Regulations and passed the associated examination with a score of 70% or better.

EPA AHERA/Nebraska Asbestos Inspector Refresher Course

Midwest Training Institute, Inc.

10731 Mockingbird Drive

Omaha, NE 68127

(402) 505-2940

(402) 515-0585

www.midwesttrainingsite.com

Course Location:

Omaha, NE

Course Date: 06/29/2022

Examination Date: 06/29/2022

Expiration Date: 06/28/2023

Certificate # MTITB 01126

Course Length – 4 Hours

Todd Rasmussen

Instructor

State of Nebraska

Department of Health and Human Services

Division of Public Health


Dustin J Wessel

Asbestos Inspector

License #: 1207

Status: Active

Expiration: 02/11/2024



APPENDIX D

Schematics

[illegible]

SHEET TITLE
**ASBESTOS CONTAINING
 MATERIAL LOCATIONS**

SHEET OF
HA100

PROJECT TITLE	PERIOD IN/AC 0304

REPAIR HVAC B324

Project Number	SGBP 20-0041
Drawing	Final By

Plan Log
Off-B-6449
Plan Log
B324


1. THE PROJECT AREA WAS RECENTLY SURVEYED FOR ACM. REFER TO THE HAZARDOUS BUILDING MATERIALS INSPECTION REPORTS BY AMI ENVIRONMENTAL DATED SEPTEMBER 4, 2020 & NOVEMBER 22, 2022 FOR MORE INFORMATION ABOUT ACM'S & LBPS IDENTIFIED IN THE PROJECT AREA.

- [illegible]

1. CONCEALED ACP PIPE INSULATION (TSI) MAY EXIST WITHIN WALLS ABOVE CEILING. PIPE CHASES ARE NOTED ON ARCHITECTURAL DRAWINGS AND THE GENERAL CONTRACTOR SHALL BE RESPONSIBLE FOR REMOVAL OF CONCEALED ACP INSULATION. SOME EXPOSURE COORDINATION MAY BE REQUIRED TO DETERMINE IF CONCEALED ACP IS PRESENT.
2. IF CONCEALED THERMAL SYSTEM INSULATION IS FOUND DURING CONSTRUCTION, ESTABLISH REGULAR INSULATION DETECTION METHODS REQUIRED FOR SECTIONS OF PPAT TO BE DISCOVERED. WRAP AND GLOVEBOX ATTACHMENT METHODS ARE USED ONLY IF APPROVED BY THE GENERAL CONTRACTOR. USE GLOVEBOX ATTACHMENT METHOD TO REMOVE ACP THAT REMAINS IN WALL PENETRATIONS. WHEN GLOVEBOX ATTACHMENT METHOD IS USED TO REMOVE ACP, THE GENERAL CONTRACTOR SHALL BE RESPONSIBLE FOR REPAIR OF PENETRATIONS IN ACCORDANCE WITH AIAA SPECIFICATION F508.0248.00.

3. FIRE DOORS WITHIN THE PROJECT LIMITS ARE ASSUMED AQM. TESTING SHOULD BE DONE AT CONSTRUCTION PHASE OR ASSUME AQM.
4. COORDINATE NEGATIVE AIR DISCHARGE LOCATIONS WITH GENERAL CONTRACTOR, OWNERS REPRESENTATIVE, AND VPM, IF NEEDED.
5. THE ABATEMENT CONTRACTOR SHALL WORK CLOSELY WITH THE GENERAL CONTRACTOR, CONTRACTING AGENCY, OWNERS, AND THE AERIAL MONITORING CONTRACTOR TO COORDINATE MONITORING AND ABATEMENT ACTIVITIES WITH PROJECT SCHEDULING. EQUIPMENT, PERSONNEL, AND REQUIREMENTS, SOME AFTER HOURS AND WEEKEND WORK MAY BE REQUIRED. PAVING IS SUBJECT TO CHANGE TO ACCOMMODATE SITE CONDITIONS AND FACILITY OPERATIONS.

LEGEND	DESCRIPTION	FRABLE	EST. QTY.	LEGEND
1	LARGE MUDDIED FITTING (GRAY/WHITE)	NO	3 EA	
2	MUDDIED FITTING (WHITE)	NO	12 EA	
3	MUDDIED FITTING (BROWN/WHITE)	NO	6 EA	
4	MUDDIED FITTING (GRAY)	NO	39 EA	
5	EXPANSION TANK INSULATION (GRAY)	NO	225 SF	



KEY PLAN

1 BASEMENT FLOOR PLAN
SCALE: 3/32" = 1'-0"

